

Toby Floor Polish



Timber Floor Polish

Description

Toby Floor Polish is a durable polish designed to enhance the life of timber floors finished with Toby oil based products such as Toby Tung Oil and Toby Oil Modified Urethane. It produces a sacrificial, clear finish resistant to traffic scuffing. When used regularly it maintains the timber floor's new look.

Special features

- Provides a sacrificial protective coating for floors finished with Toby Tung Oil or Toby Oil Modified Urethane
- Easy to apply
- Adds years to the life of floors
- Returns floor's 'new' look
- Available in gloss and satin

Properties

Appearance:	Milky white liquid
Finish:	Gloss and satin
Density:	1.04 g/ml
Viscosity:	13 seconds (Ford #4 cup)
Packaging:	1 litre plastic bottle 5 litre plastic bottle
Flammability:	Non-flammable
Shelf life:	12 months in unopened can (correctly stored)

Directions for use

Surface preparation

New Floors coated with Toby Tung Oil or Toby Oil Modified Urethane:

Allow at least 7 days for the coating to fully cure. Ensure surface is free of contaminants. It may be necessary to damp mop the floor using Toby Polyclean as per label instructions, then apply Toby Floor Polish as per application instructions.

Existing Floors:

Ensure surface is free of contaminants. Use Toby Floor Stripper as per label instructions to remove old polish or wax. Damp mop the floor using Toby Polyclean as per label instructions, then apply Toby Floor Polish as per application instructions.

Application

- Apply 2-3 thin coats of Toby Floor Polish using a premium grade cotton mop. Remove any fluff from mop prior to use
- Allow sufficient drying time between coats, approximately 1 hour
- For full gloss effect, burnish final coat (ensure sufficient drying time has been allowed) at 1000 rpm or greater if burnisher available

Coverage: 50 - 80 m²/litre

Clean up: Water

Storage: Protect from extremes of temperature. Store between 5°C and 30°C

Care and maintenance

To extend the life of the floor, use floor-glides under chair and furniture legs and follow a regular maintenance programme along the following lines.

Daily

Sweep the floor daily with an electrostatic mop. Spot mop any spillages using Toby Polyclean.

Weekly

Floor should be damp mopped using Toby Polyclean. Burnish floor for full gloss effect.

(In high traffic/commercial environments it may be desirable to polish weekly to fortnightly).

Monthly to Quarterly

Wash floor with Toby Polyclean. Apply two coats of Toby Floor Polish as per instructions.

Annual Maintenance

Wash and strip the floor with Toby Floor Stripper. Apply two fresh coats of Toby Floor Polish.

Periodic Maintenance

Depending on traffic wear, wash and strip using Toby Floor Stripper. Sand floor with 150 grit screenback, use steel wool for edges. Thoroughly vacuum the floor to remove all dust then apply one coat of Toby Tung Oil or Oil Modified Urethane (whichever was used originally) as per label instructions, then apply Toby Floor Polish as per above instructions.

Note: In low traffic domestic environments floors will only need stripping and polishing as per the above procedure every 2-3 years.

Toby Floor Polish



Precautions

Health and safety

No adverse effects expected if the product is handled in accordance with Material Safety Data Sheet and product label. If swallowed in large amounts, however, may cause nausea and vomiting. Contact with eyes and skin may cause irritation. If inhaled, vapour may cause irritation to mucous membrane and respiratory tract causing headache and nausea.

First Aid

If swallowed, rinse mouth with water and give plenty of water to drink. If vomiting occurs give further water. Seek medical advice. If in eyes, hold eyes open and flood with water for at least 15 minutes, call a doctor. If skin contact occurs, remove contaminated clothing and wash before re-use. If irritation occurs seek medical advice. If affected by inhalation of vapour, remove to fresh air. Seek medical advice if effects persists.

Material Safety Data Sheets (MSDS) are available to users on request to your nearest Orica Woodcare office or Toby Distributor. Read MSDS, data sheet and label carefully before first use of any product. Orica Woodcare are continually updating materials and methods, so please ensure you have the latest information.

Manufacturer's Comment

This product has been designed as part of a totally integrated application system. Use with any other manufacturer's product, or failing to follow application instructions, could result in detrimental effects on product performance, for which Orica Woodcare cannot be held responsible.

Orica Woodcare
A.B.N. 99 004 117 828
1330 Ferntree Gully Rd
SCORESBY VIC 3179

Email: toby_enquiries@orica.com
Internet: www.toby.com.au

7 days a week
Technical Support Hotline : 1800 073 530 Emergency Response: 1800 033 111 (24hrs)

Important note

Orica Woodcare products are guaranteed against defective materials and manufacture and are sold subject to its standard terms and conditions of sale, copies of which may be obtained on request. Whilst the company endeavours to ensure that any advice, recommendation, specification or information it may give is accurate and correct, it cannot, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products, whether or not in accordance with any advice, specification, recommendation or information given by it.